

Firebox T115-W

Wi-Fi 7 built in and 3 x 1Gb ports. Silent, fanless design with 4GB RAM for fast, secure performance in compact branch environments.



Affordable Security without Compromise

Perfect for solo professionals and micro-offices, the T115-W offers robust protection and performance designed for low-traffic environments. As the most cost-effective option in its category, it includes all essential security features, along with secure boot and an ultra-quiet fan, making it ideal for silent, space-constrained setups.

We use WatchGuard firewalls at multiple locations. These models vary from small to large but we use the full security suite at all sites.

These firewalls are easy to configure but offer exception value in the security elements that the full suite adds.

This all comes at a cost point much lower than the competition.

~Verified User

Firebox T115-W	Technical Specifications		
Throughput ¹			
UTM (full scan) ²	280 Mbps		
Firewall (IMIX)	320 Mbps		
VPN (IMIX)	210 Mbps		
HTTPS (IPS enabled, full scan)	140 Mbps		
Antivirus	450 Mbps		
IPS (full scan)	375 Mbps		
Firewall (UDP 1518)	1.02 Gbps		
VPN (UDP 1518)	640 Mbps		
Capacity			
Network Interfaces	3		
I/O interfaces	1 Serial/1 USB-A 3.2		
Concurrent connections	3,850,000		
Concurrent connections (proxy)	120,000		
New connections per second	26,500		
VLANs	Unlimited		
WSM licenses (incl)	0		
EDR Core Sensors included	0		
VPN Tunnels			
Branch Office VPN	5		
Mobile VPN	5		
Security Features			
Firewall	Stateful packet inspection, TLS decryption, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS, and Explicit Proxy		
	IMAPS, and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
Visibility			
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3		
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary, and visibility tools		
. •	1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		

Firebox T115-W		Technical Specifications			
Certifications					
Security		Pending: CC, FIPS 140-2			
Safety		NRTL/CB			
Network		IPv6 Ready Gold (routing)			
Hazardous substance control		WEEE, RoHS, REACH			
Networking					
SD-WAN		Multi-wan failover, dynamic path selection, jitter/loss/latency measurement			
Dynamic Routing		RIP, OSPF, BGP			
High Availability		Active/passive, active/active			
QoS		802.1Q, DSCP, IP Precedence			
Traffic Management		By policy or application			
IP address assignment		Static, DHCP (server, client, relay), PPPoE, DynDNS			
NAT		Static, dynamic, 1:1, IPSec traversal, policy- based			
Link aggregation		802.3ad d	ynamic, static, active/backup		
Physical and Power	Specification	าร			
Product Dimensions		8" x 6.85" x 1.65" (205 x 174 x 42mm)			
Shipping Dimension		10 x 10.5" x 2" (255 x 267 x 51 mm)			
Product Weight		1.75 lbs (0.80 kg)			
Shipping Weight		2.75 lbs (1.25 kg)			
Power Consumption		25 Watts (Max)			
Power	ower		100-240 VAC Autosensing		
Environment	Operating		Storage		
Temperature	32° F to 104 0° C to 40° (-40° F to 158° F -40° C to 70° C		
Relative Humidity	10% to 85% non-conden	sing	10% to 85% non-condensing		
Altitude	0 to 9,843 ft	at 95° F	0 to 15,000 ft at 95° F		

(4,570 m at 35° C)





Strong Security at Every Layer

(3,000 m at 35° C)

701,687 hours

Altitude

MTBF

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing, and much more.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard. com/sizing to access the online Product Sizing Tool.

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

	Standard Support	Basic Security	Total Security
Stateful Firewall	/	/	<u>√</u>
VPN	✓	✓	✓
SD-WAN	✓	✓	✓
Access Portal*	✓	✓	✓
Intrusion Prevention Service (IPS)		✓	✓
Application Control		✓	✓
WebBlocker		✓	✓
spamBlocker		✓	✓
Gateway AntiVirus		✓	✓
Reputation Enabled Defense		1	✓
Network Discovery		✓	✓
APT Blocker			✓
DNSWatch			✓
IntelligentAV**			✓
ThreatSync (XDR)			✓
EDR Core			✓
WatchGuard Cloud Log Data Retention Report Data Retention		90 Days 1 Day	365 Days 30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

^{*}Not available on Firebox T115-W, T20/T20-W, T25/T25-W, or T35-R. Total Security Suite required for M270, M370, M470, M570, M670,

¹ Throughput rates are determined using multiple flows through multiple ports and will vary depending on the environment and configuration. Max firewall throughput tested via direct connection using 1518-byte UDP frames based on RFC 2544 methodology. All testing performed on Fireware version 2025.1.

² UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

FireboxV and Firebox Cloud.
**Not available on Firebox T115-W, T20/T20-W, T25/T25-W, or T35-R.