

Firebox T185

Available with built-in SFP+ interface, 2.5Gb ports, 4GB RAM, and up to 1.83 Gbps UTM for high-demand sites. Plus, faster BOVPN performance.



Enterprise-Grade Security for Branch Offices and Retail Environments

The Firebox T185 is the most powerful tabletop firewall in the Firebox T Series, designed to handle heavier traffic loads in demanding environments. It features SFP+ fiber, providing flexible, high-performance connectivity tailored to your network needs. Plus, it includes a highly reliable built-in power supply and a Kensington Lock to ensure the device's physical security..

"We use WatchGuard firewalls at multiple locations. These models vary from small to large but we use the full security suite at all sites.

These firewalls are easy to configure but offer exception value in the security elements that the full suite adds.

This all comes at a cost point much lower than the competition."

~Verified User

Firebox T185	Technical Specifications
Throughput ¹	
UTM (full scan) ²	1.83 Gbps
Firewall (IMIX)	5.70 Gbps
VPN (IMIX)	1.14 Gbps
HTTPS (IPS enabled, full scan)	1.00 Gbps
Antivirus	2.80 Gbps
IPS (full scan)	2.40 Gbps
Firewall (UDP 1518)	7.90 Gbps
VPN (UDP 1518)	2.20 Gbps
Capacity	
Interfaces	4 x 1 GbE, 4 x 2.5 GbE, 1 x SFP/SFP+
I/O interfaces	1 Serial/2 USB-A 3.2
Concurrent connections	3,850,000
Concurrent connections (proxy)	130,000
New connections per second	26,500
VLANs	Unlimited
WSM licenses (incl)	4
EDR Core Sensors included	50
VPN Tunnels	
Branch Office VPN	100
Mobile VPN	100
Security Features	
Firewall	Stateful packet inspection, TLS decryption, proxy firewall
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS and Explicit Proxy
Threat Protection	DoS attacks, fragmented & malformed packets blended threats
Filtering Options	Browser Safe Search, Google for Business
VPN	
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke
Remote Access VPN	IKEv2, IPSec, L2TP, TLS
Visibility	
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary and visibility tools
· •	

Firebox T185		Technical Specifications			
Certifications					
Security		Pending: CC, FIPS 140-3			
Safety		NRTL/CB			
Network		IPv6 Ready Gold (routing)			
Hazardous substance control		WEEE, RoHS, REACH			
Networking					
SD-WAN		Multi-wan failover, dynamic path selection, jitter/loss/latency measurement			
Dynamic Routing		RIP, OSPF, BGP			
High Availability		Active/passive, active/active			
QoS		802.1Q, DSCP, IP Precedence			
Traffic Management		By policy of	or application		
IP address assignment		Static, DHCP (server, client, relay), PPPoE, DynDNS			
NAT		Static, dynamic, 1:1, IPSec traversal, policy- based			
Link aggregation		802.3ad dynamic, static, active/backup			
Physical and Power	Specification	าร			
Product Dimensions		13" x 8.35" x 1.7" (330 x 212 x 44 mm)			
Shipping Dimension		17.0"x 12.0"x 5.3" (435 x 306 x 135 mm)			
Product Weight		5.33 lbs (2.43 kg)			
Shipping Weight		7.26 lbs (3.30 kg)			
Power Consumption		25 Watts (no PoE) 90 Watts (PoE)			
Power	Power		100-240 VAC Autosensing		
Environment	Operating		Storage		
Temperature	32° F to 104 0° C to 40° (-40° F to 158° F -40° C to 70° C		
Relative Humidity	10% to 85% non-conden		10% to 85% non-condensing		
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)		0 to 15,000 ft at 95° F (4,570 m at 35° C)		
MTBF	172,411 ho				





Strong Security at Every Layer

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses again advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing, and much more.

- 1 Throughput rates are determined using multiple flows through multiple ports and will vary depending on the environment and configuration. Max firewall throughput tested via direct connection using 1518-byte UDP frames based on RFC 2544 methodology. All testing performed on Fireware version 2015.
- 2 UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard. com/sizing to access the online Product Sizing Tool.

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

	Standard	Basic	Total
	Support	Security	Security
Stateful Firewall	✓	✓	✓
VPN	✓	✓	✓
SD-WAN	✓	✓	✓
Access Portal*	✓	✓	✓
Intrusion Prevention Service (IPS)		✓	✓
Application Control		✓	✓
WebBlocker		✓	✓
spamBlocker		✓	✓
Gateway AntiVirus		✓	✓
Reputation Enabled Defense		/	1
Network Discovery		✓	✓
APT Blocker			1
DNSWatch			✓
IntelligentAV**			✓
ThreatSync (XDR)			✓
EDR Core			✓
WatchGuard Cloud Log Data Retention Report Data Retention		90 Days 1 Day	365 Days 30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

"Not available on Firebox T115-W, T20/T20-W, T25/T25-W, or T35-R. Total Security Suite required for M270, M370, M470, M570, M670, Firebox V and Firebox Cloud

FireboxV and Firebox Cloud.

**Not available on Firebox T115-W, T20/T20-W, T25/T25-W, or T35-R.